

Technical details

Superior XR 6.5 GF, 2025

Specification: **XR 6.5 GF**

BASE INFO

WEIGHT 10.35 kg

ISO and EN norm

ISO norm ISO 4210-2 Road Racing bicycles

EN norm EN17406 Condition 6 Suitable Road Riding

LOAD CAPACITY 120 Kg

FRAMESET

FRAME Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready

FORK X-ROAD Carbon Fork

BOTTOM BRACKET SHIMANO BB-RS501, BSA, shell 68mm

HEADSET ACROS AIX-643, ICR, OD56, IS52/28.6 - 40IPS

FRONT AXLE SB02, TA12x119, M12xP1.5x8.5L, Black

REAR AXLE SB02, TA12x165, M12xP1.5x14L, Black

DRIVETRAIN

SHIFTERS LEFT SHIMANO 105 R7120, 2-speed

SHIFTERS RIGHT SHIMANO 105 R7120, 12-speed

FRONT DERAILLEUR SHIMANO 105 FD-R7100, Down Swing, Down Pull, Brazed-On Type

REAR DERAILLEUR SHIMANO 105 RD-R7100, Shadow Design

CRANKSET SHIMANO 105 FC-R7100, Hollowtech II

CASSETTE SHIMANO 105 CS-R7101, 12 speed, 11-34T

CHAIN SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT SHIMANO 105 R7120, hydraulic disc brake

ROTOR FRONT SHIMANO SM-RT70, 160mm

BRAKE REAR SHIMANO 105 R7120, hydraulic disc brake

ROTOR REAR SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE

RIM FRONT DT Swiss R500, Disc, 28H, Tubeless Ready

TIRE FRONT Schwalbe One Performance, RaceGuard, 30-622, ADDIX

HUB REAR SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE

RIM REAR DT Swiss R500, Disc, 28H, Tubeless Ready

TIRE REAR Schwalbe One Performance, RaceGuard, 30-622, ADDIX

SPOKES SAPIM Race, Stainless Black

NIPPLES SAPIM, Alloy

COCKPIT

STEM ONE Race ICR, Alloy, 31,8mm, -7°

HANDLEBAR ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°

GRIPS LEFT ONE Handlebar Tape

PARTS

SADDLE Selle Royal SRX, 148mm

SEATPOST ONE Race, Alloy, 27.2mm

SEATPOST CLAMP ONE CC-080A, 31.8mm, Black