

Technical details

Superior XR 6.3 GR, 2025

Specification: **XR 6.3 GR**

BASE INFO

WEIGHT 11.05 kg

ISO and EN norm

ISO norm ISO 4210-2 Road Racing bicycles

EN norm EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm

LOAD CAPACITY 120 Kg

FRAMESET

FRAME Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready

FORK XR Carbon Fork

BOTTOM BRACKET SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm

HEADSET ACROS AIX-318R1, ICR, OD56, IS52/28.6 - 40IPS

FRONT AXLE SB02, TA12x119, M12xP1.5x8.5L, Black

REAR AXLE SB02, TA12x165, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT SHIMANO CUES U6030, 11-speed

REAR DERAILLEUR SHIMANO CUES RD-U6000, Shadow Plus Design

CRANKSET SHIMANO CUES FC-U6030, 42T

CASSETTE SHIMANO CUES CS-LG400, 11-speed, 11-50T

CHAIN KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT SHIMANO CUES U6030, hydraulic disc brake

ROTOR FRONT SHIMANO SM-RT54, 160mm

BRAKE REAR SHIMANO CUES U6030, hydraulic disc brake

ROTOR REAR SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE

RIM FRONT STARS J21DC, Disc, 28H

TIRE FRONT Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX

HUB REAR SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE

RIM REAR STARS J21DC, Disc, 28H

TIRE REAR Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX

SPOKES SAPIM Race, Stainless Black

NIPPLES SAPIM, Brass

COCKPIT

STEM ONE Race ICR, Alloy, 31,8mm, -7°

HANDLEBAR ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°

GRIPS LEFT ONE Handlebar Tape

PARTS

SADDLE Selle Royal SRX, 148mm

SEATPOST ONE Race, Alloy, 27.2mm

SEATPOST CLAMP ONE CC-080A, 31.8mm, Black